



Tipología de fabricación electrofundido (Todas las medidas son en mm.)



Nominal	Distancia entre ejes		Pletina portante	Ø Separador entregirado	Luz de malla libre	kg/m ²
	Pletina portante	Ø Separador				
20x20	21	24	25x2	liso	18x18	20
20x20	21	24	25x2	e./t.	18x18	20
			30x3	e./t.	18x18	42
30x15	34,3	19,2	30x2	e./t.	31,3x13,2	24
			30x3	e./t.	31,3x13,2	33
30x30	34,3	38,1	20x2	e./t.	32,3x33,1	14
			20x3	e./t.	31,3x32,1	21
			25x2	e./t.	32,3x32,1	19
			25x3	e./t.	31,3x32,1	25
			30x2	e./t.	32,3x32,1	22
			30x3	e./t.	31,3x32,1	29
			35x3	e./t.	31,3x32,1	31
			40x3	e./t.	31,3x32,1	37
			40x4	e./t.	30,3x32,1	49
			50x4	e./t.	30,3x32,1	60
			30x5	e./t.	29,3x30,1	41
			40x5	e./t.	29,3x30,1	60
			45x5	e./t.	29,3x30,1	68
			60x5	e./t.	29,3x30,1	88
30x60	34,3	76,2	20x2	e./t.	32,3x70,2	12
			25x2	e./t.	32,3x70,2	17
			25x3	e./t.	31,3x70,2	23
			30x2	e./t.	32,3x70,2	20
			30x3	e./t.	31,3x70,2	27
			40x3	e./t.	31,3x70,2	36
60x5	e./t.	31,3x70,2	85			
30x100	34,3	101,6	30x3	e./t.	31,3x95,6	26
30x30	34,3	38,1	25x2 dentado	e./t.	31,3x32,1	19
			25x3 dentado	e./t.	31,3x32,1	25
			30x3 dentado	e./t.	31,3x32,1	29
			40x3 dentado	e./t.	31,3x32,1	37
30x60	34,3	76,2	25x2 dentado	e./t.	32,3x70,2	17
			30x3 dentado	e./t.	31,3x70,2	27
40x40	42	44	25x2	liso	39x39	13
60x60	62	66	25x2	liso	59x61	10
			25x3	liso	59x61	12
60x120	62	132	25x2	liso	59x127	9
			25x3	liso	59x127	11
30x30	34,3	38,1	30x2 8x8 p.p.	e./t.	32,3x32,1	24
			30x3 8x8 p.p.	e./t.	31,3x32,1	31
			30x3 8x8dent	e./t.	31,3x32,1	31



Se pueden suministrar otros materiales no detallados en esta tabla, en acabados: bruto, galvanizado o lacado (escala RAL) infórmese llamando a oficinas

Proceso de galvanizado:

